Regulation EC No 1907/2006 Art.31

Productname :	Ink & Paint Remover	Creationdate :	29.06.17 Version : 3.0
Ref.Nr.:	BDS001187_3_20170629 (EN)	Replaces:	BDS001187_20150326

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Ink & Paint Remover Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

Cleaners - Precision

1.3. Details of the supplier of the safety data sheet

CRC Industries Europe bvba Touwslagerstraat 1 9240 Zele Belgium Tel.: +32(0)52/45.60.11 Fax.: +32(0)52/45.00.34 E-mail : hse@crcind.com

Subsidiaries		Tel	Fax
CRC Industries Finland Oy	Laurinkatu 57 A 23 B, 08100 Lohja	+358/(19)32.921	
CRC Industries France	6, avenue du marais, C.S. 90028, 95102 Argenteuil Cedex	01.34.11.20.00	01.34.11.09.96
CRC Industries Deutschland GmbH	Südring 9, D-76473 Iffezheim	(07229) 303 0	(07229)30 32 66
CRC INDUSTRIES IBERIA S.L.U.	GREMIO DEL CUERO-PARC.96, POLIGONO INDUSTR. DE HONTORIA, 40195 SEGOVIA	0034/921.427.546	0034/921.436.270
CRC Industries Sweden	Laxfiskevägen 16, 433 38 Partille	0046/31 706 84 80	0046/31 27 39 91

1.4. Emergency telephone number

CRC Industries Europe, Belgium: Tel.: +32(0)52/45.60.11 (office hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Physical:

Aerosols, category 1 Extremely flammable aerosol. Pressurised container: May burst if heated.

Classification is based on test data.



Safety Data Sheet		Regulation EC No 1907/2006 Art.31		
Productname :	Ink & Paint Remover	Creationdate :	29.06.17 Version : 3.0	
Ref.Nr.:	BDS001187_3_20170629 (EN)	Replaces:	BDS001187_20150326	

Health:	Eye irritation, category 2 Causes serious eye irritation. Hazardous to the aquatic environment, chronic category 3 May cause drowsiness or dizziness.
Classification based on c Environment:	
Classification based on c	alculation method.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008

Product identifier:	Contains:
Hazard pictogram(s):	acetone; propan-2-one; propanone
nazaru pictogram(s).	
Signal word:	Danger
Hazard statement(s):	H222 : Extremely flammable aerosol.
	H229 : Pressurised container: May burst if heated.
	H319 : Causes serious eye irritation.
	H336 : May cause drowsiness or dizziness.
Precautionary statement(s):	P102 : Keep out of reach of children.
	P210 : Keep away from heat, hot surfaces, sparks, open flames and other
	ignition sources. No smoking.
	P211 : Do not spray on an open flame or other ignition source.
	P251 : Do not pierce or burn, even after use.
	P261 : Avoid breathing dust/fume/gas/mist/vapours/spray.
	P271 : Use only outdoors or in a well-ventilated area.
	P410/412 : Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
	P501-2 : Dispose of contents/container to an authorised waste collection point.
Supplemental Hazard information:	Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

No information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable.

3.2. Mixtures

Hazardous ingredient	Registration number	CAS-nr. EC-nr	w/w %	Hazard Class and Category	Hazard statement	Notes
CR®		ries Europe bv 1, 9240 Zele – Belgin +32) (0) 52 / 45 00 34	um	w.crcind.com	2/9	,

Productname :	Ink & Paint Remover	Creationdate :	29.06.17 Version : 3.0
Ref.Nr.:	BDS001187 3 20170629 (EN)	Replaces:	BDS001187 20150326
	BB6001107_0_20170020 (EN)	Replaces.	BB6001101_20100020

01-2119471330- 49	67-64-1	200- 662-2	75- 100	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3	H225,H319,H336	A
01-2119485926- 20	68512- 91-4	270- 990-9	10- 25	Press. Gas, Flam. Gas 1	H280,H220	K,G
Explanation notes						
A : substance with Community workplace exposure limit						
G : exempted from the obligation to register in accordance with art.2(7)of REACH Regulation No 1907/2006						
K : not classified as carcinogen, less than 0.1% w/w 1,3-butadiene (Einecs-nr. 203-450-8)						
	49 01-2119485926- 20 re limit cordance with art.2	49 67-64-1 01-2119485926- 20 91-4 re limit cordance with art.2(7)of REA	49 67-64-1 662-2 01-2119485926- 68512- 270- 20 91-4 990-9	49 67-64-1 662-2 100 01-2119485926- 68512- 270- 10- 20 91-4 990-9 25	49 67-64-1 662-2 100 2, STOT SE 3 01-2119485926- 68512- 270- 10- Press. Gas, Flam. 20 91-4 990-9 25 Gas 1	49 67-64-1 662-2 100 2, STOT SE 3 H225,H319,H336 01-2119485926- 20 68512- 91-4 270- 990-9 10- 25 Press. Gas, Flam. Gas 1 H280,H220 re limit cordance with art.2(7)of REACH Regulation No 1907/2006

(* Explanation phrases : see chapter 16)

SECTION 4: First aid measures

4.1. Description of first aid measures

Contact with eyes :	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Contact with skin :	Take off contaminated clothing and wash before reuse. IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.
Inhalation :	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Ingestion :	If swallowed accidentally, do not induce vomiting and seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation :	Excessive inhalation of solvent vapours may give rise to nausea, headaches and dizziness
Ingestion :	May cause gastrointestinal disturbances Symptoms : sore throat, abdominal pain, nausea, vomiting
Skin contact :	May cause irritation. Symptoms : redness and pain
Eye contact :	Irritating to eyes Symptoms : redness and pain

4.3. Indication of any immediate medical attention and special treatment needed

General Advice :	If you feel unwell, seek medical advice (show the label where possible
	If symptoms persist always call a doctor

SECTION 5: Firefighting measures

5.1. Extinguishing media

foam, carbon dioxide or dry agent

5.2. Special hazards arising from the substance or mixture

Aerosols may explode if heated above 50°C



Productname :	Ink & Paint Remover	Creationdate :	29.06.17 Version : 3.0
Ref.Nr.:	BDS001187_3_20170629 (EN)	Replaces:	BDS001187 20150326
	DD0001107_5_20170025 (LIN)	Replaces.	DD0001107_20130320

Forms hazardous decomposition products CO,CO2

5.3. Advice for firefighters

Keep container(s) exposed to fire cool, by spraying with water In case of fire, do not breathe fumes

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Shut off all ignition sources Ensure adequate ventilation Wear suitable protective clothing and gloves.

6.2. Environmental precautions

Do not allow to enter public sewers and watercourses If polluted water reaches drainage systems or water courses, immediately inform appropriate authorities

6.3. Methods and material for containment and cleaning up

Absorb spillage in suitable inert material Place in appropriate container

6.4. Reference to other sections

For further information see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep away from heat and sources of ignition Take precautionary measures against static discharges Equipment should be earthed Use explosion-proof electrical/ventilating/lighting/.../equipment. Use only non-sparking tools. Do not breathe aerosols or vapours. Ensure adequate ventilation Avoid contact with skin and eyes. Wash thoroughly after use Wear protective gloves/protective clothing/eye protection/face protection. Eyewash bottles should be available

7.2. Conditions for safe storage, including any incompatibilities

Pressurized container : protect from sunlight and do not expose to temperatures exceeding 50°C.



Productname :	Ink & Paint Remover	Creationdate :	29.06.17 Version : 3.0
Ref.Nr.:	BDS001187_3_20170629 (EN)	Replaces:	BDS001187 20150326
	DD0001107_0_20170029 (LIN)	Replaces.	DD0001107_20100320

Keep out of reach of children.

7.3. Specific end use(s)

Cleaners - Precision

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits :

Hazardous ingredient	CAS-nr.	method	
EU established exposure limits:			
acetone; propan-2-one; propanone	67-64-1	TWA	500 ppm
National established exposure limits, United Kingdom		2	
acetone; propan-2-one; propanone	67-64-1	TWA	500 ppm
		STEL	1500 ppm

8.2. Exposure controls

Control procedures :	Ensure adequate ventilation Keep away from heat and sources of ignition Take precautionary measures against static discharges
Personal protection :	Take precautions to avoid contact with skin and eyes when handling the product. Ensure adequate ventilation Wear suitable protective gloves
inhalation :	In case of insufficient ventilation, wear suitable respiratory equipment.
recommended respiratory protection:	Air purifying respirator equiped with organic gas/vapor cartridge (type AX)
hands and skin :	When handling the product wear chemical-resistant gloves (standard EN 374). The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through.
Recommended gloves:	(butyl rubber)
eyes :	Wear safety eyewear according to EN 166.
Environmental protection:	Avoid release to the environment. Collect spillage.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

(for aerosols data for the product without propellant)		
Apperance : physical state : Liquid.		
colour :	Colorless.	
odour :	Characteristic odor.	
pH : Not applicable.		



Productname :	Ink & Paint Remover	Creationdate :	29.06.17 Version : 3.0
Ref.Nr.:	BDS001187_3_20170629 (EN)	Replaces:	BDS001187_20150326

Boiling point/range :	56 °C
Flash point :	- 18 °C
Evaporation rate :	Not available.
Explosion limits : upper limit :	13 %
lower limit :	1.8 %
Vapour pressure :	24.1 kPa (@ 20°C).
Relative density :	0.79 g/cm3 (@ 20°C).
Solubility in water :	Partly soluble in water
Auto-ignition :	515 °C
Viscosity :	Not available.

9.2. Other information

VOC = volatile organic 740 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reactions known if used for its intended purpose

10.2. Chemical stability

Stable

10.3. Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose

10.4. Conditions to avoid

Avoid overheating

10.5. Incompatible materials

Strong oxidising agent

10.6. Hazardous decomposition products

CO,CO2

SECTION 11: Toxicological information

11.1. Information on toxicological effects

acute toxicity:based on available data the classification criteria are not metskin corrosion/irritation:based on available data the classification criteria are not met



Safety Data Sheet		Regulation EC No 1907/2006 Art.31		
Productname :	Ink & Paint Remover	Creationdate :	29.06.17 Version : 3.0	
Ref.Nr.:	BDS001187_3_20170629 (EN)	Replaces:	BDS001187_20150326	

serious eye damage/irritation:	Causes serious eye irritation.
respiratory or skin sensitisation:	based on available data the classification criteria are not met
germ cell mutagenicity:	based on available data the classification criteria are not met
carcinogenicity:	based on available data the classification criteria are not met
toxicity for reproduction:	based on available data the classification criteria are not met
STOT-single exposure:	May cause drowsiness or dizziness.
STOT repeated exposure:	based on available data the classification criteria are not met
aspiration hazard:	based on available data the classification criteria are not met

Information on likely routes of exposure:

Inhalation :	Inhalation of solvent vapours may give rise to nausea, headaches and dizziness
Ingestion :	May cause gastrointestinal disturbances
Skin contact :	May cause irritation.
Eye contact :	Irritating to eyes

Toxicological data :

Hazardous ingredient	CAS-nr.	method	
acetone; propan-2-one; propanone	67-64-1	LD50 oral rat	> 5800 mg/kg
		LC50 inhal.rat	76 mg/l
		LD50 derm.rabit	> 15800 mg/kg

SECTION 12: Ecological information

12.1. Toxicity

Not classified

Ecotoxicological data:

Hazardous ingredient	CAS-nr.	method	
acetone; propan-2-one; propanone	67-64-1	IC50 algae	530 mg/l
		LC50 fish	5540 mg/l
		EC50 daphnia	8800 mg/l

12.2. Persistence and degradability

No experimental data available

12.3. Bioaccumulative potential

No experimental data available

12.4. Mobility in soil



Productname :	Ink & Paint Remover	Creationdate :	29.06.17 Version : 3.0
Ref.Nr.:	BDS001187_3_20170629 (EN)	Replaces:	BDS001187_20150326

Soluble in water

12.5. Results of PBT and vPvB assessment

No information available

12.6. Other adverse effects

No experimental data available

SECTION 13: Disposal consid	Jerations
13.1. Waste treatment methods	
Product :	This material and its container must be disposed of in a safe way. Do not discharge into drains or the environment, dispose to an authorised waste collection point.
National regulations :	Disposal should be in accordance with local, state or national legislation
SECTION 14: Transport infor	mation
14.1. UN number	
UN-number :	1950
14.2. UN proper shipping name	
Proper shipping name:	AEROSOLS
14.3. Transport hazard class(es)	
Class: ADR/RID - Classification code:	2.1 5F

14.4. Packing group

Packing group: Not applicable.

14.5. Environmental hazards

ADR/RID - Environmentally hazardous:	No
IMDG - Marine pollutant:	No
IATA/ICAO - Environmentally	No
hazardous:	INO.

14.6. Special precautions for user



Regulation EC No 1907/2006 Art.31

	Creationdate : Replaces:	29.06.17 Version : 3.0 BDS001187_20150326
--	-----------------------------	--

ADR/RID - Tunnelcode:	(D)
IMDG - Ems:	F-D, S-U
IATA/ICAO - PAX:	203
IATA/ICAO - CAO	203

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The Safety Data Sheet is compiled according to the current European requirements. Regulation (EC) No 1907/2006 (REACH) Regulation (EC) No 1272/2008 (CLP) Dir. 2013/10/EU, 2008/47/EC amendment of the aerosol dispenser directive 75/324/EEC.

15.2. Chemical safety assessment

No information available

SECTION 16: Other information

*Explanation hazard statements:	 H220 : Extremely flammable gas. H225 : Highly flammable liquid and vapour. H280 : Contains gas under pressure; may explode if heated. H319 : Causes serious eye irritation. H336 : May cause drowsiness or dizziness.
REVISIONS IN CHAPTRE :	8.2. Exposure controls
acronyms and synonyms:	TWA = time weight average STEL = short time exposure limit VOC = volatile organic compounds PBT = persistant bioaccumulative toxic vPvB = very persitant very bioaccumulative

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.

